

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

FILTER STRIP

(Ac.)

CODE 393

DEFINITION

A strip or area of herbaceous vegetation that removes contaminants from overland flow.

PURPOSE

- Reduce suspended solids and associated contaminants in runoff.
- Reduce dissolved contaminant loadings in runoff.
- Reduce suspended solids and associated contaminants in irrigation tailwater.

CONDITIONS WHERE PRACTICE APPLIES

Filter strips are established where environmentally-sensitive areas need to be protected from sediment, other suspended solids and dissolved contaminants in runoff; in areas situated below cropland, grazing land, or disturbed land (including forest land); and in areas where permanent vegetative establishment is needed to enhance wildlife and beneficial insects, or maintain or enhance watershed function.

This practice applies when planned as part of a conservation management system.

CRITERIA

General Criteria Applicable to All Purposes

Filter strips shall be designated as vegetated areas to treat runoff and are not part of the adjacent cropland rotation.

Overland flow entering the filter strip shall be uniform sheet flow. Concentrated flow shall be dispersed before entering the filter strip.

State listed noxious weeds will not be established in the filter strip and will be controlled if present. Filter strips shall not be used as a travel lane for equipment or livestock.

Filter strip establishment shall comply with local, state and federal regulations.

Additional criteria to reduce sediment, particulate organics and sediment-adsorbed contaminant loadings in runoff

Filter strip flow length shall be determined based on field slope percent and length, and filter strip slope percent, erosion rate, amount and particle size distribution of sediment delivered to the filter strip, density and height of the filter strip vegetation, and runoff volume associated with erosion producing events. The minimum flow length for this purpose shall be 20 feet.

Filter strip location requirements:

- The filter strip shall be located along the downslope edge of a field or disturbed area. To the extent practical it shall be placed on the approximate contour. Variation in placement on the contour should not exceed a 0.5% longitudinal (perpendicular to the flow length) gradient.
- The drainage area above the filter strip shall have greater than 1% but less than 10% slopes.
- The filter strip will be designed to have a 10-year life span, following the procedure in the Agronomy Technical Note No. 2 (Using RUSLE2 for the Design and Predicted Effectiveness of Vegetative Filter Strips (VFS) for Sediment), based on the sediment delivery in RUSLE2 to the upper

edge of the filter strip and ratio of the filter strip flow length to the length of the flow path from the contributing area.

- The ratio of the drainage area to the filter strip area shall be less than 70:1 in regions with RUSLE-R factor values 0-35, 60:1 in regions with RUSLE-R factor values 35-175, and 50:1 in regions with RUSLE-R factor values of more than 175.
- The average annual sheet and rill erosion rate above the filter strip shall be less than 10 tons per acre per year

Vegetation. The filter strip shall be established to permanent herbaceous vegetation.

Species selected shall be:

- able to withstand partial burial from sediment deposition and
- tolerant of herbicides used on the area that contributes runoff to the filter strip.

Species selected shall have stiff stems and a high stem density near the ground surface.

Species selected for seeding or planting shall be suited to current site conditions and intended uses. Selected species will have the capacity to achieve adequate density and vigor within an appropriate period to stabilize the site sufficiently to permit suited uses with ordinary management activities.

Species, rates of seeding or planting, minimum quality of planting stock, such as PLS or stem caliper, and method of establishment shall be specified before application. Only viable, high quality seed or planting stock will be used.

Site preparation and seeding or planting shall be done at a time and in a manner that best ensures survival and growth of the selected species. What constitutes successful establishment, e.g. minimum percent ground/canopy cover, percent survival, stand density, etc. shall be specified before application.

Planting dates shall be scheduled during periods when soil moisture is adequate for germination and/or establishment.

The minimum seeding and stem density shall be equivalent to a high quality grass hay seeding rate for the climate area or the density

of vegetation selected in RUSLE2 to determine trapping efficiency, whichever is the higher seeding rate.

Additional Criteria to Reduce Dissolved Contaminants in Runoff

The criteria given in “Additional criteria to reduce sediment, particulate organics and sediment adsorbed contaminant loadings in runoff” for location, drainage area and vegetation characteristics also apply to this purpose.

Filter strip flow length required to reduce dissolved contaminants in runoff shall be based on management objectives, contaminants of concern, and the volume of runoff from the filter strip’s drainage area compared with the filter strip’s area and infiltration capacity.

The flow length determined for this purpose shall be in addition to the flow length determined for reducing sediment, particulate organics and sediment-adsorbed contaminant loadings in runoff.

The minimum flow length for this purpose shall be 30 feet.

Additional Criteria to Serve as Zone 3 of a Riparian Forest Buffer, Practice Code 391

Except for the location requirements, the criteria given in “Additional criteria to reduce sediment, particulate organics and sediment adsorbed contaminant loadings in runoff” also apply to this purpose.

If concentrated flows entering Zone 3 are greater than the filter strip’s ability to disperse them, other means of dispersal, such as spreading devices, must be incorporated.

Additional Criteria to Reduce Sediment, Particulate Organics and Sediment-adsorbed Contaminant Loadings in Surface Irrigation Tailwater

Filter strip vegetation may be a small grain or other suitable annual with a plant spacing that does not exceed 4 inches.

Filter strips shall be established early enough prior to the irrigation season so that the vegetation can withstand sediment deposition from the first irrigation.

The flow length shall be based on management objectives with a minimum flow length of 20 feet.

Additional Criteria to Restore, Create or Enhance Herbaceous Habitat for Wildlife and Beneficial Insects

If this purpose is intended in combination with one or more of the previous purposes, then the minimum criteria for the previous purpose(s) must be met.

Additional filter strip flow length devoted to this purpose must be added to the length required for the other purpose(s).

Any addition to the flow length for wildlife or beneficial insects shall be added to the downhill slope of the filter strip.

Vegetation to enhance wildlife may be added to that portion of the filter strip devoted to other purposes to the extent they do not detract from its primary functions.

Plant species selected for this purpose shall be for permanent vegetation adapted to the wildlife or beneficial insect population(s) targeted.

If this is the only purpose, filter strip width and length shall be based on requirements of the targeted wildlife or insects. Density of the vegetative stand established for this purpose shall consider targeted wildlife habitat requirements and encourage plant diversity. Dispersed woody vegetation may be used to the extent it does not interfere with herbaceous vegetative growth, or operation and maintenance of the filter strip.

The filter strip shall not be mowed during the nesting season of the target wildlife.

Livestock and vehicular traffic in the filter strip shall be excluded during the nesting season of the target species.

Additional Criteria to Maintain or Enhance Watershed Functions and Values

Filter strips shall be strategically located to enhance connectivity of corridors and non-cultivated patches of vegetation within the watershed.

Filter strips shall be strategically located to enhance aesthetics of the watershed.

Plant species selected for this purpose shall be for establishment of permanent vegetation.

CONSIDERATIONS

Filter strips should be strategically located to reduce runoff, and increase infiltration and ground water recharge throughout the watershed.

Filter strip width (flow length) can be increased as necessary to accommodate harvest and maintenance equipment.

Filters strips with the leading edge on the contour will function better than those with a gradient along the leading edge.

Seeding rates that establish a higher stem density than the normal density for a high quality grass hay crop will be more effective in trapping and treating contaminants.

Creating, Restoring or Enhancing Herbaceous Habitat for Wildlife and Beneficial Insects and Pollinators. Filter strips are often the only break in the monotony of intensively-cropped areas. The wildlife and pollinator benefits of this herbaceous cover can be enhanced by:

- Increasing the width beyond the minimum required, and planting this additional area to species that can provide food and cover for wildlife and pollinators. This additional width should be added on the downslope side of the filter strip.
- Adding herbaceous plant species to the filter strip seeding mix that are beneficial to wildlife and pollinators and be compatible for one of the listed purposes. Changing the seeding mix should not detract from the purpose for which the filter strip was established.
- Filter strips for the single purposes of wildlife/beneficial insect habitat or to enhance watershed function should be strategically located to intercept contaminants thereby enhancing air and water quality.

To avoid damage to the filter strip consider using vegetation that is somewhat tolerant to herbicides used in the up-slope crop rotation.

Consider using this practice to enhance the conservation of declining species of wildlife,

including those that are threatened or endangered.

Consider using this practice to protect National Register listed or eligible (significant) archaeological and traditional cultural properties from potential damaging contaminants.

Select grass species that sequester more carbon. Increasing the width of filter strip will increase the potential for carbon sequestration.

PLANS AND SPECIFICATIONS

Based on this standard, plans and specifications shall be prepared for each specific field site where a filter strip will be installed. A plan includes information about the location, construction sequence, vegetation establishment, and management and maintenance requirements.

Specifications shall include:

- a) Length, width, and slope of the filter strip to accomplish the planned purpose (length refers to flow length across the filter strip).
- b) Species selection and seeding or sprigging rates to accomplish the planned purpose
- c) Planting dates, care and handling of the seed to ensure that planted materials have an acceptable rate of survival
- d) A statement that only viable, high quality and regionally adapted seed will be used
- e) Site preparation sufficient to establish and grow selected species

OPERATION AND MAINTENANCE

For the purposes of filtering contaminants, permanent filter strip vegetative plantings should be harvested as appropriate to encourage dense growth, maintain an upright growth habit and remove nutrients and other contaminants that are contained in the plant tissue.

Control undesired weed species, especially state-listed noxious weeds.

Prescribed burning may be used to manage and maintain the filter strip when an approved burn plan has been developed.

Inspect the filter strip after storm events and repair any gullies that have formed, remove unevenly deposited sediment accumulation that will disrupt sheet flow, reseed disturbed areas and take other measures to prevent concentrated flow through the filter strip.

Apply supplemental nutrients as needed to maintain the desired species composition and stand density of the filter strip.

To maintain or restore the filter strip's function, periodically regrade the filter strip area when sediment deposition at the filter strip-field interface jeopardizes its function, and then reestablish the filter strip vegetation, if needed. If wildlife habitat is a purpose, destruction of vegetation within the portion of the strip devoted to that purpose should be minimized by regrading only to the extent needed to remove sediment and fill concentrated flow areas.

Grazing shall not be permitted in the filter strip unless a controlled grazing system is being implemented. Grazing will be permitted under a controlled grazing system only when soil moisture conditions support livestock traffic without excessive compaction.

REFERENCES

Dillaha, T.A., J.H. Sherrard, and D. Lee. 1986. Long-Term Effectiveness and Maintenance of Vegetative Filter Strips. VPI-VWRRRC Bulletin 153.

Dillaha, T.A., and J.C. Hayes. 1991. A Procedure for the Design of Vegetative Filter Strips: Final Report Prepared for U.S. Soil Conservation Service.

Foster, G.R. Revised Universal Soil Loss Equation, Version 2 (RUSLE2) Science Documentation (In Draft). USDA-ARS, Washington, DC. 2005.

Renard, K.G., G.R. Foster, G.A. Weesies, D.K. McCool, and D.C. Yoder, coordinators. 1997. Predicting Soil Erosion by Water: A Guide to Conservation Planning with the Revised Universal Soil Loss Equation (RUSLE). U.S. Department of Agriculture. Agriculture Handbook 703.